

GTR-AR-5498-G2-T3



FITTED PLATE-(PLAT)



SCREW IN YOKE - (SOLY)E39 SHOWN



Description and Application:

LED Retrofit Kit for Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

Specification Features:

- Available with Custom fitted aluminum plate, universal plate or universal bracket.
- Custom colors available upon request.

Mounting Options:

- PLAT = Custom Plate
- UVSB = Universal Shoe Box Plate
- UVBR = Universal Bracket
- SOLY = Yoke Mount (E39)

Driver and Wattage:

120-277vAC 150w input / 24vDC output constant current

Additional Information:

Warranty:
Driver - 5 year warranty
Solstice Light Engine - 10 year warranty

LED and Optical Assembly: Structured LED Clusters for Optimized Photometric performance

0 - 10V Dimming Capable

Lumen Depreciation:
System rating is L70 at 100,000hrs.

- Surge Protector:
- Required for ALL 347V-480V applications in order to qualify for Warranty
- Recommended for all outdoor applications

Ordering Code Example:

GTR-AR - 5498-G2 - HO - SV - BL - T3 - PLAT

Fixture	Wattage			Color Temp	Optics	Mounting Method
Fixture	LED Model #	Wattage Output	Diver Input Voltage	Kelvin	Optics	Mounting Method
GTR-AR	5498-G2	HO = (95W)	SV = 120-277V	BL = 4000K (80CRI)	T3 = Type 3 Optics	PLAT
		HI = (85W)				UVSB
		MH = (75W)				UVBR
						SOLY



Fully Compliant with ARRA Buy American Requirements. Made in the USA.