

GENERAL INFORMATION

LED Driver Type	Constant Voltage (LVLE)
Maximum Wattage	192 Watts
Input Voltage	120 - 277 VAC ± 10% Universal
Input Frequency	50/60Hz
Total Harmonic Distortion	<20%

CASE STYLE NN: METAL



ELECTRICAL SPECIFICATIONS

Watts	Output Voltage	Max Output Current	Input Voltage	Input Power	Input Current	Power Factor	Efficiency	Hatch Part Number
192W	24 VDC	8.00A	120 - 277 VAC	208W	1.74/0.75A	>0.99	92%	LV192-24N-UNV-NN

PRODUCT FEATURES

- Short circuit and overload protection
- Over temperature protection
- Suitable for dry, damp and wet locations
- Withstanding voltage: I/P – O/P 2kVAC
- Minimum start temp: -30°C

APPROVALS

- UL 8750 recognized component
- EN61000-3-2
- EMC: Meets FCC47 CFR Part 15 (Class B) consumer limits
- IP67



WARRANTY

- 5 year limited warranty

MECHANICAL SPECIFICATIONS: CASE STYLE NN

WIRING INFORMATION

Input: Type SJTW, 12", Black (L), White (N) Green (GND) #18AWG
 Output: Type SJTW, 12", Red (+), Black (-) #14AWG

PACKAGING INFORMATION

Weight: 40.0 oz
 Quantity: 20pc/carton

