

GTR-AR-M21



Description and Application:

LED Retrofit Kit for Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

Specification Features:

Available with Custom fitted aluminum plate, universal plate or universal bracket. Custom colors available upon request.

Mounting Options:

- PLAT = Custom Plate
- UVSB = Universal Shoe Box Plate
- UVBR = Universal Bracket
- SOLY = Yoke Mount (E39)

Driver and Wattage:

120-277vAC 60w input / 24vDC output
120-277vAC 40w input / 24vDC output

Additional Information:

Warranty:
Driver - 5 year warranty
Solstice Light Engine - 10 year warranty

LED And Optical Assembly:
Structured LED Clusters for
Optimized Photometric

Lumen Depreciation:
System rating is L70 at
100,000hrs.

Surge Protector:
- Recommended for all outdoor
applications

Ordering Code Example:

GTR-AR - M21 - HO - SV - GR - NL - PLAT

Fixture	LED Model #	Wattage Output	Diver Input Voltage	Color Temp Kelvin	Optics	Mounting Method
GTR-AR	M21	LO = (75W)	SV = 120-277V	GR = 5000K (70CRI)	NL = No Lens 360s = Square Side Emitters	PLAT
		ML = (40W)		BR = 5000K (80CRI)		UVSB
	M21	MH = (50W)	SV = 120-277V	YW = 4100K (70CRI)	T2 = Type II	UVBR
	M21	HI = (60W)		BL = 4000K (80CRI)		SOLY



Fully Compliant with ARRA Buy American Requirements. Made in the USA.