



# IESNA LM79-2008 Test Report

TÜV SÜD America

## Photometric Testing and Evaluation in Accordance with LM79-2008

Report Prepared for:

**Michael Prainito**  
Marketing Manager

**Global Tech LED LLC**  
8901 Quality Road  
Bonita Springs, FL 34135  
United States

Telephone: (877) 748-5533

**Sample Tested:** GTSOL5498-TURTLE  
**Sample Description:** LED Module  
**Manufacturer:** Global Tech LED LLC

**Technical Report Number:** 72105196-01-LM79  
**Report Issue Date:** April 27<sup>th</sup>, 2015  
**Total Number of Pages:** 8 (including this page)

Report Prepared by:

**Tim Gentry**  
TÜV SÜD Project Handler

Report Reviewed by:


**Ben Ferrell**  
TÜV SÜD Program Manager

## IESNA LM79-2008 TEST REPORT

April 8th, 2015

### Summary of Key Test Results

Model# **GTSOL5498-TURTLE**  
 Manufacturer **Global Tech LED LLC**  
 TÜV Sample# 1789-1  
 Date of Test April 21, 2015  
 Notes: Tested in intended orientation  
 (Aperture Down)



Parameter	Measured Result
Luminous Flux	<b>542.3 Lumens</b>
Input Power	<b>80.09 Watts</b>
Efficacy	<b>6.45 Lumens/Watt</b>
C.C.T.	<b>1249 K</b>
C.R.I. (R <sub>a</sub> )	<b>7.3</b>
Beam Angle	<b>118.7° (V) / 119.4° (H)</b>
Stabilization Time	<b>60 minutes</b>

The above results are recorded / derived from measurements in accordance with LM79-08. The testing contained within this report was conducted with the LED module energized by a constant voltage LED driver manufactured by Hatch, Model LV100-24N-UNV-I.



# IESNA LM79-2008 TEST REPORT

April 8th, 2015

## TABLE OF CONTENTS

Test Results .....4

Spectral Flux and Chromaticity Diagram .....5

Zonal Lumen Summary .....5

Illuminance Plots.....6

Candela Plots .....6

Equipment List: .....8





# IESNA LM79-2008 TEST REPORT

April 8th, 2015

**Test Results–**

The following results were obtained after stabilization of the sample in accordance with the requirements set forth in section 5.0 of IES LM79-2008. Stability is achieved when the variation of 3 readings of light output and electrical power over a period of 30 minutes, taken 15 minutes apart, is less than 0.5%.

Photometric Results	GTSOL5498-TURTLE	
	Integrating Sphere	
Total Luminous Flux (Lumens)	542.3	
Luminous Efficacy (Lumens/Watt)	6.45	
Correlated Color Temperature (CCT)	1249	
Color Rendering Index (CRI – R <sub>a</sub> )	7.3	
R <sub>9</sub> Value	-312.8	
Total Radiant Flux (Watts)	1.3	
Chromaticity (Chroma x / Chroma y)	0.6226	0.3766
Chromaticity (Chroma u / Chroma v)	0.3969	0.3602
Chromaticity (Chroma u' / Chroma v')	0.3969	0.5402
D <sub>uv</sub> Value	0.00159	

Electrical Results	GTSOL5498-TURTLE	
	Integrating Sphere (120V / 277V)	
Input Power (Watts)	84.09	83.51
Input Voltage (Volts AC)	119.98	277.01
Input Current (Amps)	0.7035	0.3180
Power Factor	0.997	0.947
A-THD (Current %)	7.76	10.68
Input Frequency (Hertz)	60.0	60.0

Additional Parameters	GTSOL5498-TURTLE	
	Integrating Sphere	Goniophotometer
Stabilization Time (Light and Power)	60 minutes	40 minutes
Test Geometry Configuration	4π	Type C
Ambient Temperature	24.2°C	24.1°C
Spacing Criteria	1.26 (0° – 180°) / 1.28 (90° – 270°)	




# IESNA LM79-2008 TEST REPORT

April 8th, 2015


## Spectral Flux and Chromaticity Diagram

### Spectral Flux



**Spectral response of the Radiant Flux**  
**(350nm to 850nm)**

### Chromaticity Diagram



**Chromaticity Coordinates (from page 4):**

$$x / y = 0.4008 / 0.3863$$

The locations on the diagram of the chromaticity coordinates are indicated by the blue diamond.

## Zonal Lumen Summary



Zone	Lumens	% Lamp / Luminaire
0 - 60	391.5	72.0%
60 - 90	150.6	27.7%
0 - 90	542.0	99.7
90 - 180	1.7	0.3 %
0 - 180	543.7	100%

# IESNA LM79-2008 TEST REPORT

April 8th, 2015


## Test Results – Illuminance Plots

The following images depict the illuminance characteristics of the luminaire.




## Test Results – Candela Plots


The following images depict the luminous intensity distribution characteristics of the luminaire:



Isofootcandle Plot



Isocandela Plot



Polar Candela

Maximum Candela = **169.0** at Horizontal: 0°, Vertical: 0°



# IESNA LM79-2008 TEST REPORT

April 8th, 2015

## TÜV SÜD Photometric Testing Information

Testing is performed in accordance with the procedures outlined in IESNA LM79-2008. The sample is evaluated for photometric and electrical characteristics using an integrating sphere and a goniophotometer, located in an accredited, temperature and humidity-controlled, draft free photometric laboratory.

### *Sphere Geometry*

The integrating spheres used for measurement utilize a “ $4\pi$  geometry” configuration in accordance with section 9 of IES LM-79-2008 and is applicable for all types of SSL products (directional and non-directional light projections). The spectroradiometer is an array-type detector manufactured and calibrated by Labsphere (Model# CDS1100).

### *Self-Absorption Correction*

The integrating sphere uses self-absorption correction to eliminate errors due to mismatches between the standard reference lamp and the test samples being measured. This auxiliary correction lamp is a halogen type lamp powered by a calibrated Lamp Power Supply manufactured and calibrated by Labsphere (model LPS150). Ambient temperature is measured using a thermocouple located inside the integrating sphere at the same height as the sample under test (UUT) and not more than 1 meter in horizontal distance away from the sample (section 2.2 of LM79-2008). The thermocouple is located behind a baffle in order to eliminate any direct optical radiation from the sample under test.

### *Sample Stabilization*

The sample (UUT) is placed inside the integrating sphere and powered by a regulated and conditioned alternating or direct current supply. The stabilization times shown on the results pages of this report denote the time of the 3<sup>rd</sup> measurement (of the 3 consecutive readings) since this is the minimum time that the sample is assumed to have taken to reach stabilization in accordance with section 5.0 of LM79-2008.

### *Sphere Calibration*

The integrating sphere is calibrated using a quartzline halogen lamp with the following specifications:

Manufacturer: EYE Lighting International

Model# J94/JD28V75W

Voltage = 28.0 Volts DC

Wattage = 75.0 Watts

Calibration Current = 2.679 Amperes

Luminous Flux = 1685 Lumens

Calibration Date = 2-17-2011 (calibrated by Labsphere – NIST traceable).

Continued.....

#### **TÜV SÜD America, Inc.**

5945 Cabot Parkway, Suite 100,  
Alpharetta GA 30005

Telephone: 678-341-5900 www.tuvamerica.com

Page 7

NRG\_F\_10.04

**Confidential Report**



TÜV SÜD America is  
accredited under the  
ISO/IEC 17025:2005  
program



# IESNA LM79-2008 TEST REPORT

April 8th, 2015

## TÜV SÜD Photometric Testing Information (continued)

### Goniophotometer

The Goniophotometer is a Mirror based Type C optical measurement system in accordance with section 9.3.1 of IESNA LM79-2008.

### Goniophotometer Calibration

The Goniophotometer is calibrated using a frosted tungsten filament FDS/DZE lamp with the following specifications:

- Manufacturer: General Electric
- Part Number: CSB-110
- Lamp Number: 112-A
- Voltage: 16.52 Volts DC
- Wattage: 150.0 Watts
- Calibration Current: 4.816 Amperes
- Luminous Intensity: 151.5 Candelas
- Calibration Date: 02-13-2011 (NIST traceable)

## TÜV SÜD Test Equipment List:

<b>TÜV SÜD Sphere System – contains the following:</b>			
Description	Manufacturer / Model#	TÜV SÜD Ref#	Calibration Due Date
Integrating Sphere	Labsphere LM760	SPH003	weekly
Power Analyzer	Yokogawa WT210	ATLE0058	3/7/2016
Power Source	Chroma 61602	AC003	N/A
Thermometer	Fluke 52-II	ATLE0008	11/17/2015
<b>TÜV SÜD Mirror Goniophotometer System – contains the following:</b>			
Goniophotometer	M.E. GONC02	GON002	Weekly
Spectroradiometer	Gigahertz Optik P9801	GIG002	Weekly
Power Analyzer	Yokogawa WT210	ATLE0031	11/16/2015
Power Source	Chroma 61603	AC007	N/A

*This technical report may only be quoted in full. Any use for advertising purposes must be granted in writing. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production.*

*This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government*

